



## WSA 306

# ASV module for smoke panels



Natural  
ventilation



Smoke  
ventilation

### Application

Integrated in smoke control panels to ensure a cable surveillance.

The smoke detector input can be used for transmitting on a signal from an external fire detecting system (ASV). This requires a potential-free ASV contact and the ASV module.

#### ASV OPEN function

To generate a trip (EMERGENCY OPEN) of the smoke ventilation group actuating the potential-free contact in the ASV. All smoke ventilation actuators "OPEN" automatically. The ventilation buttons are now out of operation. The break glass unit has priority than an ASV trip.

#### ASV CLOSE function

It is also possible to have a ASV CLOSE function.

To generate a trip (EMERGENCY CLOSE) of the smoke ventilation group actuating the potential-free contact in the ASV. All smoke ventilation actuators "CLOSE" automatically. The ventilation buttons are now out of operation. The break glass unit has priority than an ASV trip.

Contact WindowMaster for further information.

ASV module for WSC 204, WSC 304 61, WSC 310 P, WSC 320 P and FlexiSmoke™ WSC 5xx.

WSA 306

# ASV module for smoke panels

Items	Item no.
ASV-module for WSC 204, WSC 304 16, WSC 310 P, WSC 320 P and FlexiSmoke™ WSC 5xx	WSA 306

We reserve the right to make technical changes