



WSC 204: opens during smoke
WSC 204BZ: closes during smoke



WSC 204MH: opens during smoke,
steel housing

1.05

WSC 204 / WSC 204BZ / WSC 204MH Smoke control panel 4.8A



Natural
ventilation



Smoke ventilation
EN 12101



Rated voltage



Maksimal
output current

Application

- 1 smoke / comfort ventilation group
- control of window actuators up to 4.8A
- with microprocessor
- smoke extraction and comfort ventilation in smaller and medium sized buildings
- expandable with additional modules
- incl. 2 pcs. back-up batteries type WSA 003

Smoke control panel for control of 24V DC actuators for smoke extraction and daily comfort ventilation.

The smoke control panel is especially suitable for surveillance of smaller areas, e.g. staircases, smaller sport centres and restaurants.

WSC 204 / WSC 204BZ / WSC 204KP

The smoke control panel is supplied in plastic housing and can be either countersunk mounted or surface mounted (frame for surface mounting is supplied).

WSC 204

The smoke control panel opens the windows actuators during smoke.

WSC 204BZ

The smoke control panel closes the windows actuators during smoke.

WSC 204MH

The smoke control panel opens the windows actuators during smoke. The smoke control panel is supplied in steel housing and is suitable for surface mounting.

Extension

By linking several smoke control panels in a master/slave system, the smoke control unit can also be used in larger buildings (master/slave module type WSA 301 required).

Special technical features

- approval according to EN 12101-10
- for smoke extraction combined with comfort ventilation
- built-in uninterruptible power supply 2 pcs. WSA 003 (min. 72h battery back-up in case of voltage loss)
- cable surveillance on break glass unit
- cable surveillance on smoke detector input (if used)
- survey on actuator outlet
- breakage of smoke signal lines 1 and 2 are seen separately via diodes on the bottom plate
- fault display via diagnostic LEDs
- incident reporting is programmable as smoke triggering
- smoke triggering when temperature inside the compact unit exceeds 72°C

Connection options

- actuator with end switch or electrical load switch of
- tripping by BMS via potential-free contact (ASV module WSA 306 required)
- in connection with comfort ventilation signals from BMS units can be received
- wind/rain sensor without additional plug in module
- 15 ventilation keypads with "indicator" or as many "open" indicators
- 10 smoke detectors type WSA 311 or WSA 310
- 4 break glass units (primary), type WSK 320 or type WSK 321
- 15 break glass units (secondary), type WSK 330

Technical specifications

Output current	Max. 4.8A	
Primary voltage	230V AC $\pm 10\%$, 150W, 50/60Hz $\pm 10\%$	
Actuator secondary voltage	Rated voltage Open circuit voltage at 230V AC Open circuit voltage at 253V AC Motor voltage at 230V AC / 4.8A load Ripple at max. load (4.8V) Open circuit voltage at battery operation	24V typ. 28V DC max. 31.3V DC typ. 22V DC max.6% (= 3.8Vpp) min. 18.7V DC
Inrush current	Max. 6A < 5msec	
Standby consumption	4W	
Emergency power supply	>72h	
Operating condition	-5°C - +40°C, max. 90% relative humidity (not condensing)	
Switch-on-duration	ED max. 40% (max. 4 min per 10 min)	
Material	WSC 204 / WSC 204BZ: plastic housing for countersunk or surface mounting WSC 204MH: steel housing for surface mounting	
Colour	WSC 204 / WSC 204BZ: white (RAL 9016) WSC 204MH: grey (RAL 7035)	
Size	WSC 204 / WSC 204BZ: 368 x 353mm (W x H) Surface mounting D=97mm Countersunk mounting D=95mm, hole in wall 325 ± 5 x 311 ± 5 x min. 80mm (W x H x D) WSC 204MH: 300 x 300 x 120mm (WxHxD)	
Weight	WSC 204 / WSC 204BZ: 4.7kg excl. batteries / 7.5kg incl. batteries WSC 204MH: 6kg excl. batteries / 10kg incl. batteries	
IP rating	WSC 204 / WSC 204BZ (plastic housing): IP30 WSC 204MH (steel housing): IP54	
Approval / certification	WSC 204 / WSC 204BZ: approved according to EN 12101-10	
Delivery includes	Smoke control panel with 2 pcs. back-up batteries 12V/3.4Ah (2 x WSA 003) WSC 204 / WSC 204BZ: supplied with a plastic frame for surface mounting	
Spare parts	See the spare part list on our web site www.windowmaster.com under "Products"	
Note	We reserve the right to make technical changes	

WSC 204 / WSC 204BZ / WSC 204MH

Smoke control panel 4.8A

Items	Item no.
Smoke panel 4.8A, plastic housing	WSC 204 0102
Smoke panel 4.8A, plastic housing, closes in case of smoke (<i>primary for CH</i>)	WSC 204BZ 0102
Smoke panel 4.8A, metal housing	WSC 204MH 0102

Accessories	Item no.
Smoke detector	WSA 311
Alarm and fault module (master/slave)	WSA 301
Linking of wind/rain signal	WSA 302
Time ventilation module	WSA 303
Gap ventilation module	WSA 304B
ASV module	WSA 306
End module	WSA 432
Smoke detector end module	WSA 433
See separate product sheets for further information	