



Black anodized aluminium ■



WLL 121 – Extension cable.




WLL 121E1 – Extension cable
with entrapment connection
via the extra 2 core cables.



WLL 121E2 – Extension cable
with entrapment connection
via the extra short cable.

WMX 813

Chain actuator



1.43

Description

- optimized design for concealed installation
- for smoke and comfort ventilation
- to be used with all window types
- to be used together with $\pm 24V$ control units or control units with MotorLink®
- can be used together with locking actuators WMB
- external safety edge can be connected directly to the actuator (actuator version 'E')
- synchronization of up to four window actuators – no need for an external synchronization module
- genuine position feedback and three speeds when using control unit with MotorLink®
- soft close
- the electronics in this actuator can be programmed to suit specific requirements – i.e. pressure- and traction force, stroke, speed/sound level.
- built-in electronic load switch-off/end stop
- electronic actuator with micro controller
- the actuator has an integrated reverse function to ensure a prolonged life span of the window gaskets

Actuator variants

The actuator is available in four different versions:
single actuator (-1), double actuator (-2), triple actuator (-3)
and quad actuator (-4).

The synchro actuators (-2, -3 and -4) are equipped with a synchronization function, in which the actuators communicate directly with each other, which ensures the actuators operate at exactly the same speed and position.

On large windows up to four actuators can be mounted on the same window – with no need for an external synchronization module.

Pressure safety function

The risk of entrapment is reduced as the actuators are programmed to reverse if they encounter obstacles when closing.


Opening speeds

Actuators connected to ± 24 VDC control units (e.g. WCC 103) can be run with one speed.

Actuators connected to control units with MotorLink® (e.g. WCC 3xx or 106) can be run with three different speeds:

- automatically control speed – actuators run slowly and almost soundlessly.
- manual control speed – actuators run faster and more audibly.
- H&S and safety control speed – actuators run fastest. H&S control always has highest priority.

| Technical specifications | |
|----------------------------------|---|
| Pressure force | See diagram |
| Traction force | See diagram |
| Locking force | 2000N |
| Chain opening | 50 – 1000mm in increments of 10mm, maximum opening depends on the window construction |
| Opening speed | 1-17 mm/s (TrueSpeed™) |
| Sound pressure level | ≤25 dBA (operational speed: 1 mm/s), ≤42 dBA (operational speed: 10 mm/s) |
| Window type | Concealed installation |
| Nominal voltage | 24V DC (max. 10% ripple) |
| Voltage | 20-36V DC |
| Max. open-circuit voltage | max. 36V DC |
| Current consumption | max. 1A |
| Working condition | -5°C - +74°C, max. 90% relative humidity (not condensing) |
| Switch-on-duration | ED 40% (max. 4 min. per 10 min). If speed < 20% ED 100%. |
| Material | Aluminium, steel chain, silicone cable |
| Colour | Black anodized aluminium E6/EV1, black RAL 9005. Other RAL colours available at additional price |
| Size | 22 x 33mm (H x D), length (L) depending on chain stroke – see table. |
| Weight | 400mm stroke: 1.28 kg; 600mm stroke: 1.42 kg; 800mm stroke: 1.63 kg; 1000mm stroke: 1.84 kg; |
| IP rating | concealed: IP 32 |
| SHE test | Approved according to EN 12101-2 with selected profiles – please contact WindowMaster for further information B300 tested according to EN 12101-2 |
| Delivery includes | WMX 813 Z: Actuator with 35mm connection cable (3-core cables 0.34mm ²) with Molex Micro-Fit connector for WLL cables WMX 813 E: Actuator with 35mm connection cable (3-core cables 0.34mm ²) with Molex Micro-Fit connector for WLL cables and connection for safety device |
| To be ordered separately | Brackets and standard extension cables (WLL) |
| Note | We reserve the right to make technical changes and correct typing errors |



The sound pressure level was measured externally by The Danish Technological Institute. The measurements have been carried out in a large regular room size 7 x 14 x 2.4 m (W x L x H) with the ceiling covered with a standard sound absorbent material. The A-weighted sound pressure levels have been measured at a distance of 1 meter away from the surface of the actuators and at the height of 1.6 meters from the floor. The actuators were not installed on any window profile nor added any load. The full opening and full closing sound of the actuators have been measured and the result represents the average of the measurements.

| Product code composition | | | | | | |
|--|----|---|------|---|---|---|
| WMX 813 | -n | x | yyyy | z | v | 1 |
| Product version: 1 | | | | | | |
| Certification: 0 = CE, P = CE + EN 12101-2 | | | | | | |
| Actuator hardware version: Z = cable not included, E = with connection for safety device | | | | | | |
| Chain opening: 50 – 1000mm, in increments of 10mm (0050 = 50mm) | | | | | | |
| Colour: B = black anodized aluminium | | | | | | |
| Actuator variant: 1= single, 2 = double, 3 = triple, 4 = quad | | | | | | |

Explanation of product code structure


WMX 813-2B0070Z P1 WMX 813 actuator, double synchronisation, black, 70mm chain opening, standard without cable, with CE and EN 12101-2 certification, product version 1.

WMX 813-2B0070E P1 WMX 813 actuator, double synchronisation, black, 70mm chain opening, with connection for safety device, without cable, with CE certification, product version 1.



| Items | Chain stroke [mm] | Length (L) [mm] (incl. screws = 18mm) | Item no. without cable | Item no. with connection for safety device |
|-----------------|-------------------|--|---------------------------|---|
| Single actuator | 400 | 499 | WMX 813-1B0400Z P1 | WMX 813-1B0400E P1 |
| | 600 | 599 | WMX 813-1B0600Z P1 | WMX 813-1B0600E P1 |
| | 800 | 699 | WMX 813-1B0800Z P1 | WMX 813-1B0800E P1 |
| | 1000 | 799 | WMX 813-1B1000Z P1 | WMX 813-1B1000E P1 |
| Double actuator | 400 | 499 | WMX 813-2B0400Z P1 | WMX 813-2B0400E P1 |
| | 600 | 599 | WMX 813-2B0600Z P1 | WMX 813-2B0600E P1 |
| | 800 | 699 | WMX 813-2B0800Z P1 | WMX 813-2B0800E P1 |
| | 1000 | 799 | WMX 813-2B1000Z P1 | WMX 813-2B1000E P1 |
| Triple actuator | 400 | 499 | WMX 813-3B0400Z P1 | WMX 813-3B0400E P1 |
| | 600 | 599 | WMX 813-3B0600Z P1 | WMX 813-3B0600E P1 |
| | 800 | 699 | WMX 813-3B0800Z P1 | WMX 813-3B0800E P1 |
| | 1000 | 799 | WMX 813-3B1000Z P1 | WMX 813-3B1000E P1 |
| Quad actuator | 400 | 499 | WMX 813-4B0400Z P1 | WMX 813-4B0400E P1 |
| | 600 | 599 | WMX 813-4B0600Z P1 | WMX 813-4B0600E P1 |
| | 800 | 699 | WMX 813-4B0800Z P1 | WMX 813-4B0800E P1 |
| | 1000 | 799 | WMX 813-4B1000Z P1 | WMX 813-4B1000E P1 |

| Accessoires | Item no. |
|---|-----------|
| Actuator bracket for WMX 813, Wicona WICLINE 75 EVO, fixed mounting | WAB 813C |
| Bracket set for WMX 813, Schüco TipeTronic AWS 75, fixed mounting | WAB 813F |
| Extension cable | WLL 121 |
| Extension cable with entrapment connection | WLL 121E1 |
| Extension cable with entrapment connection | WLL 121E2 |
| Connection cable for 2 actuators | WLL 122 |
| Connection cable for 2 actuators with entrapment connection | WLL 122E |

Extension cables

| WLL 121 | | Material | silicone, black 5m, 3-core 0.34mm ² |
|--|--|-------------------|--|
| | | Application | extension cable |
| | | Delivery includes | 1 x cable with attached Molex Micro-Fit connector and fast-on socket |
|  | | | |
| WLL 121E1 | | Material | silicone, black 5m, 5-core 0.34mm ² (2-core for entrapment connection) |
| | | Application | extension cable |
| | | Delivery includes | 1 x cable with attached Molex Micro-Fit connector and fast-on socket |
|  | | | |
| WLL 121E2 | | Material | silicone, black 1 x 5m, 3-core 0.34mm ² 1 x 0.165m, 2-core 0.34mm ² (for entrapment connection) |
| | | Application | extension cable |
| | | Delivery includes | 2 x cable with attached Molex Micro-Fit connector and fast-on socket |
|  | | | |




Connection cables

| WLL 122 | | Material | silicone, black 1 x 1.5m, 3-core 0.34mm ² 1 x 0.15m, 3-core 0.34mm ² |
|---|--|-------------------|---|
| | | Application | cable for 2 actuators |
| | | Delivery includes | 2 x cable with attached Molex Micro-Fit connectors |
|  | | | |
| WLL 122E | | Material | silicone, black 1 x 1.5m, 3-core 0.34mm ² 1 x 0.15m, 3-core 0.34mm ² 1 x 0.165m, 2-core 0.34mm ² (for entrapment connection) |
| | | Application | cable for 2 actuators |
| | | Delivery includes | 3 x cable with attached Molex Micro-Fit connectors |
|  | | | |

WMX 813




Chain actuator

Installation suggestion 1 - Inward Opening




WAB 813C

Installation suggestion 2 - Inward Opening



WAB 813F



L = Length (incl. screws) – see table of items

